

3EG-EA Flex-Shaft



- 1-1/2 HP, 115V/230V changeover switch, 3,450 RPM, 60 Hz, single phase, AC electric motor (P.N. FS102)
- Three caster swiveling tripod motor mount with carrying handle (P.N. 3927)
- 7' flexible housing (P.N. 57143A)
- Wet angle head, 4 spline, 1:1 ration (P.N. 56934)
- Multiple mounting options available

- Fits 4 spline drive shafts.
- Spindle arbors have standard 5/8"-11 thread shaft to accommodate 5/8" thread insert cup type and 5/8" bushed hole edge type grinding wheels.
- Or 3/4" pilot thread to accommodate 3/4" bushed hole cup and edge type grinding wheels.

3/4" Thread	5/8" Thread	Spindle Description
3430W	56885	Cove Base, Wet, 1:1, 3,450 RPM
3430D	56890	Cove Base, Dry, 1:1, 3,450 RPM
23500-S	56902	Straight, Dry, 1:1, 3,450 RPM
30811B	56930	Angle, Dry, 1:1, 3,450 RPM
	56930A	Angle, Dry, 2:1, 1,725 RPM
	56930B	Angle, Dry, 4:1, 865 RPM
3115B	56934	Angle, Wet, 1:1, 3,450 RPM
	56934A	Angle, Wet, 2:1, 1,725 RPM
	56934B	Angle, Wet, 4:1, 865 RPM
22610B	56959E	Angle, Dry, 10:1, 345 RPM

Optional shafts (4 spline) and housing for 3EG-EA, 1EG, 3EG Base Machines

Part #	Description
32952	7/16" diameter X 6' long flexible shaft
32952A	7/16" diameter X 7' long flexible shaft
32952B	7/16" diameter X 12' long flexible shaft
57143	6' flexible housing
57143A	7' flexible housing
57143C	12' flexible housing

95+ YEARS



Terrco® Inc.

222 1st Avenue NW • Watertown, SD 57201

Phone: (605) 882-3888 • Fax: (605) 882-0778

Website: www.terrco.us • Email: info@terrco.us

